

# xghost IP20



see also **xghost IP65**  
at page 608




**EN**  
Wall recessed light fittings for interior, equipped with SMD LEDs.  
Housing of die-cast aluminum, electrostatically painted.  
Recessed box in polycarbonate.  
Transparent diffuser of polycarbonate.  
Driver included.  
Rubber seal at cable crossing.  
Cable length 10cm, 2x0.75 mm².  
**Range of applications**  
Indoor decorative lighting.

**RO**  
Corpuri de iluminat încastrate în perete, de interior, echipate cu LED-uri SMD.  
Corp din aluminiu turnat, vopsit în câmp electrostatic.  
Doza de încastrare din policarbonat.  
Dispersor transparent din policarbonat.  
Alimentator inclus.  
Garnitură din cauciuc la trecerea cablului de alimentare.  
Lungime cablu 10cm, 2x0,75 mm².  
**Aplicații**  
Iluminatul decorativ de interior.

**IT**  
Apparecchi da incasso a parete, per interni, equipaggiati con LED SMD.  
Corpo in alluminio pressofuso verniciato a polveri.  
Scatola da incasso in policarbonato.  
Diffusore in policarbonato trasparente.  
Alimentatore incluso.  
Passaggio cavo di alimentazione con guarnizione in gomma.  
Lunghezza cavo 10cm, 2x0.75 mm².  
**Campi di applicazione**  
Illuminazione decorativa per interni.

GS01

FINISHING AVAILABLE  
MWH MBK



Code	Finishing	LED type	Power	Input voltage	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
GS01WWIP20 MWH	MWH	SMD 5730 EPISTAR	2W	100-240V AC	Included	208 lm	96 lm	3000K	80	Asymmetrical	87x87 mm 0,20 kg
GS01NWIP20 MWH	MWH	SMD 5730 EPISTAR	2W	100-240V AC	Included	224 lm	104 lm	4000K	80	Asymmetrical	87x87 mm 0,20 kg
GS01WWIP20 BK	MBK	SMD 5730 EPISTAR	2W	100-240V AC	Included	208 lm	96 lm	3000K	80	Asymmetrical	87x87 mm 0,20 kg
GS01NWIP20 BK	MBK	SMD 5730 EPISTAR	2W	100-240V AC	Included	224 lm	104 lm	4000K	80	Asymmetrical	87x87 mm 0,20 kg

