

xevo round

3 YEARS
WARRANTY

EN

Series of recessed light fittings for T-bar suspended ceiling or plasterboard, equipped with SMD LEDs. White frame of increased thermal resistance polycarbonate. Housing of anodized aluminum sheet acting as heat sink. For powers higher than 30W, the recessed frame is made of die-cast aluminum, electrostatically painted in white color. The body with heat sink role in die-cast aluminum painted black. White reflector made of reflective plastic sheet, diffuser of opal PMMA. Constant current LED driver delivered with the light fitting.

Range of applications

Interior general lighting.

RO

Serie de corpuri de iluminat echipate cu LED-uri SMD, pentru montaj încastrat în plafon fals casetat sau de gipscarton. Rama de culoare albă, din policarbonat cu rezistență termică mărită. Corpul cu rol de radiator pentru modulul cu LED-uri din aluminiu eloxat. Pentru puterile mai mari de 30W rama de încadrare este din aluminiu turnat, vopsită electrostatic, culoare albă. Corpul cu rol de radiator din aluminiu turnat vopsit negru. Reflector din folie reflectorizantă de culoare albă, dispersor din PMMA opal. Alimentator în curent constant livrat împreună cu corpul de iluminat.

Aplicații

Iluminatul general de interior.

IT

Serie di apparecchi a LED SMD per controsoffitto a cassettoni o cartongesso. Telaio in policarbonato bianco ad alta resistenza termica. Corpo in alluminio anodizzato con funzione di raffreddatore del modulo LED. Per potenze superiori a 30W, la cornice da incasso è realizzata in alluminio pressofuso, verniciata a polveri bianco sabbiate. Corpo con ruolo di raffreddatore in alluminio pressofuso verniciato nero. Riflettore composto da foglio in materiale plastico riflettente e diffusore in PMMA opalino. Alimentatore in corrente costante fornito con l'apparecchio.

Campi di applicazione

illuminazione generale d'interni.

xevo round





EV01

FINISHING AVAILABLE

MWH

IP20
IP44





Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV01WW	MWH	SMD 2835 EPISTAR	8W	200-240V AC	350 mA / 14-24V DC	Included	885 lm	617 lm	3000K	82	90°	Ø105 mm, 0,17 kg
EV01NW	MWH	SMD 2835 EPISTAR	8W	200-240V AC	350 mA / 14-24V DC	Included	990 lm	650 lm	4000K	80	90°	Ø105 mm, 0,17 kg

EV02

FINISHING AVAILABLE

MWH

IP20
IP44




Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV02WW	MWH	SMD 2835 EPISTAR	12W	200-240V AC	350 mA / 22-40V DC	Included	1290 lm	856 lm	3000K	82	90°	Ø125 mm, 0,21 kg
EV02NW	MWH	SMD 2835 EPISTAR	12W	200-240V AC	350 mA / 22-40V DC	Included	1445 lm	887 lm	4000K	80	90°	Ø125 mm, 0,21 kg

EV03

FINISHING AVAILABLE

MWH

IP20
IP44




Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV03WW	MWH	SMD 2835 EPISTAR	15W	200-240V AC	350 mA / 30-40V DC	Included	1700 lm	1154 lm	3000K	82	90°	Ø145 mm, 0,26 kg
EV03NW	MWH	SMD 2835 EPISTAR	15W	200-240V AC	350 mA / 30-40V DC	Included	1900 lm	1251 lm	4000K	80	90°	Ø145 mm, 0,26 kg

EV04

FINISHING AVAILABLE

MWH

IP20
IP44





Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV04WW	MWH	SMD 2835 EPISTAR	18W	200-240V AC	350 mA / 40-60V DC	Included	2040 lm	1422 lm	3000K	82	90°	Ø165 mm, 0,35 kg
EV04NW	MWH	SMD 2835 EPISTAR	18W	200-240V AC	350 mA / 40-60V DC	Included	2280 lm	1551 lm	4000K	80	90°	Ø165 mm, 0,35 kg

EV05

FINISHING AVAILABLE

MWH

IP20
IP44





Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV05WW	MWH	SMD 2835 EPISTAR	22W	200-240V AC	350 mA / 40-60V DC	Included	2490 lm	1820 lm	3000K	82	90°	Ø200 mm, 0,67 kg
EV05NW	MWH	SMD 2835 EPISTAR	22W	200-240V AC	350 mA / 40-60V DC	Included	2790 lm	1875 lm	4000K	80	90°	Ø200 mm, 0,67 kg

EV06

FINISHING AVAILABLE

SWH

IP44





Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV06WW	SWH	SMD 2835 BRIDGELUX	30W	200-240V AC	750 mA / 30-43V DC	Included	4032 lm	3209 lm	3000K	90	90°	Ø155 mm, 0,73 kg
EV06NW	SWH	SMD 2835 BRIDGELUX	30W	200-240V AC	750 mA / 30-43V DC	Included	4200 lm	3314 lm	4000K	90	90°	Ø155 mm, 0,73 kg

EV07

FINISHING AVAILABLE

SWH

IP44





Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV07WW	SWH	SMD 2835 BRIDGELUX	40W	200-240V AC	1000 mA / 30-42V DC	Included	5400 lm	4283 lm	3000K	90	90°	Ø200 mm, 1,05 kg
EV07NW	SWH	SMD 2835 BRIDGELUX	40W	200-240V AC	1000 mA / 30-42V DC	Included	5580 lm	4403 lm	4000K	90	90°	Ø200 mm, 1,05 kg

EV08

FINISHING AVAILABLE

SWH

IP44



Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
EV08WW	SWH	SMD 2835 BRIDGELUX	60W	220-240V AC	1400 mA / 30-42V DC	Included	7680 lm	6112 lm	3000K	90	90°	Ø200 mm, 1,08 kg
EV08NW	SWH	SMD 2835 BRIDGELUX	60W	220-240V AC	1400 mA / 30-42V DC	Included	8160 lm	6316 lm	4000K	90	90°	Ø200 mm, 1,08 kg