

**Luminaire**

Code FX22NW90

Name XFACTORY

**Measur.**

Code FX22NW90

Name XFACTORY

Luminaire Flux	25457.53 lm	Luminaire Power	200.00 W	Efficacy	127.29 lm/W	Efficiency	87.00%
Lamps Flux	29262.00 lm	Maximum value	438.33 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	400 mm	Width	400 mm	Height	1 mm
Rectangular Luminous Area		Length	400 mm	Width	400 mm	Height	0 mm
Horizontal Luminous Area	0.160000 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.038708 m2
Coordinate system	CG	Symmetry Type		Maximum Gamma Angle		Measurement Flux	Rotosymmetrical
Date	13-01-2020	Measurement Flux		Measurement Flux		Measurement Flux	180
Measurement Distance	0.00	Measurement Flux		Measurement Flux		Measurement Flux	29262.00 lm
Operator		Source Voltage [V]		Source current [A]		Photocell	
Temperature	25.00 °C	Source current [A]		Photocell			
Humidity	60.00 %	Photocell					
Notes							

Line		Code		Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
		FX22NW90		XFACTORY		29262.00	200.00	1
C.I.E.	66 92 99 100 87			D DIN 5040		A50		
F UTE	0.87 C			B NBN		BZ 2		

