

**Luminaire**

Code KA01UWW  
Name XKAPPA

**Measur.**

Code KA01UWW  
Name XKAPPA

|   |           |   |                |   |                |   |                 |
|---|-----------|---|----------------|---|----------------|---|-----------------|
| Luminaire Flux  | 366.91 lm | Luminaire Power                           | 5.00 W         | Efficacy  | 73.38 lm/W     | Efficiency                                | 99.16%          |
| Lamps Flux  | 370.00 lm | Maximum value                             | 3513.88 cd/klm | Position  | C=0.00 G=0.00  | CG  | Rotosymmetrical |
| Round Luminaire<br>Round Luminous Area  |           | Diam.<br>Diam.                            | 91 mm<br>91 mm | Height<br>Height  | 10 mm<br>10 mm |   |                 |
| Horizontal Luminous Area<br>Emitting area on Plane 0°<br>Emitting area on Plane 90° |           | 0.006504 m2<br>0.000910 m2<br>0.000910 m2 |                | Emitting area on Plane 180°<br>Emitting area on Plane 270°<br>Glare area at 76° |                | 0.000910 m2<br>0.000910 m2<br>0.002456 m2 |                 |
| Coordinate system<br>Date<br>Measurement Distance                                   |           | CG<br>03-06-2020<br>0.00                  |                | Symmetry Type<br>Maximum Gamma Angle<br>Measurement Flux                        |                | Rotosymmetrical<br>180<br>381.00 lm       |                 |
| Operator<br>Temperature<br>Humidity<br>Notes  |           | 25.00 °C<br>60.00 %                       |                | Source Voltage [V]<br>Source current [A]<br>Photocell                           |                |   |                 |

| Luminaire Lamps |                  |        |           |          |      |            |
|-----------------|------------------|--------|-----------|----------|------|------------|
| Line            | Code             | Name   | Flux [lm] | Pow. [W] | Q.ty |            |
|                 | KA01UWW          | XKAPPA | 370.00    | 5.00     | 1    |            |
| C.I.E.          | 95 98 100 100 99 |        |           |          |      | D DIN 5040 |
| F UTE           | 0.99 A           |        |           |          |      | B NBN      |
|                 |                  |        |           |          |      | A60        |
|                 |                  |        |           |          |      | BZ 1       |

