

Luminaire

Code KA02UWW
Name XKAPPA

Measur.

Code KA02UWW
Name XKAPPA

Luminaire Flux	727.25 lm	Luminaire Power	10.00 W	Efficacy	72.72 lm/W	Efficiency	99.90%
Lamps Flux	728.00 lm	Maximum value	4514.90 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	120 mm 120 mm	Height Height	10 mm 10 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.011310 m2 0.001200 m2 0.001200 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.001200 m2 0.001200 m2 0.003900 m2	
Coordinate system Date Measurement Distance		CG 03-06-2020 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 753.00 lm	
Operator Temperature Humidity Notes		25.00 °C 60.00 %		Source Voltage [V] Source current [A] Photocell			

Luminaire Lamps						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
	KA02UWW	XKAPPA	728.00	10.00	1	
C.I.E. F UTE	97 99 100 100 100 1.00 A					D DIN 5040 B NBN A60 BZ 1

