

Luminaire

Code KA04UWW
Name XKAPPA

Measurement

Code KA04UWW
Name XKAPPA

Luminaire Flux	1832.09 lm	Luminaire Power	25.00 W	Efficacy	73.28 lm/W	Efficiency	99.95%
Lamps Flux	1833.00 lm	Maximum value	2201.75 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	178 mm 178 mm	Height Height	1 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.024885 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.006020 m2	
Coordinate system Date Measurement Distance		CG 03-06-2020 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1904.00 lm	
Operator Temperature Humidity Notes		25.00 °C 60.00 %		Source Voltage [V] Source current [A] Photocell			

Luminaire Lamps						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
	KA04UWW	XKAPPA	1833.00	25.00	1	
C.I.E.	96 99 100 100 100					D DIN 5040
F UTE	1.00 A					B NBN
						A60
						BZ 1

