

**Luminaire**

 Code PXR02CCT  
 Name XPILL ROUND

**Measur.**

 Code PXR02CCT  
 Name XPILL ROUND

Luminaire Flux	5003.80 lm	Luminaire Power	50.00 W	Efficacy	100.08 lm/W	Efficiency	99.82%
Lamps Flux	5013.00 lm	Maximum value	341.20 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	480 mm 480 mm	Height Height	10 mm 10 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.180956 m2 0.004800 m2 0.004800 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.004800 m2 0.004800 m2 0.048435 m2	
Coordinate system Date Measurement Distance		CG 06-12-2019 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 5013.00 lm	
Operator Temperature Humidity Notes		25.00 °C 60.00 %		Source Voltage [V] Source current [A] Photocell			

Line		Code	Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
		PXR02CCT	Name XPILL ROUND		5013.00	50.00	1
C.I.E.	47 78 95 99 100		D DIN 5040		A31		
F UTE	0.99 E + 0.01 T		B NBN		BZ 5		

