

**Luminaire**

Code PXR05NW  
Name XPILL ROUND

**Measur.**

Code PXR05NW  
Name XPILL ROUND

Luminaire Flux	11278.48 lm	Luminaire Power	100.00 W	Efficacy	112.78 lm/W	Efficiency	99.92%
Lamps Flux	11287.00 lm	Maximum value	341.09 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area	Diam. 980 mm Diam. 980 mm	Height	10 mm	Height	10 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.754296 m2 0.009800 m2 0.009800 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°				0.009800 m2 0.009800 m2 0.191990 m2	
Coordinate system Date Measurement Distance	CG 06-12-2019 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux				Rotosymmetrical 180 11287.00 lm	
Operator Temperature Humidity Notes	25.00 °C 60.00 %	Source Voltage [V] Source current [A] Photocell					

Line		Code	Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
		PXR05NW	Name XPILL ROUND		11287.00	100.00	1
C.I.E.	47 78 95 99 100		D DIN 5040	A31			
F UTE	0.99 E + 0.01 T		B NBN	BZ 5			

