

Luminaire

 Code PXQ04WW
 Name XPILL SQUARE

Measur.

 Code PXQ04WW
 Name XPILL SQUARE

Luminaire Flux	7845.88 lm	Luminaire Power	80.00 W	Efficacy	98.07 lm/W	Efficiency	99.95%
Lamps Flux	7850.00 lm	Maximum value	341.95 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Rectangular Luminous Area	Length Length	780 mm 780 mm	Width Width	780 mm 780 mm	Height Height	10 mm 10 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.608400 m2 0.007800 m2 0.007800 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.007800 m2 0.007800 m2 0.154754 m2				
Coordinate system Date Measurement Distance	CG 06-12-2019 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 180 8340.00 lm				
Operator Temperature Humidity Notes	25.00 °C 60.00 %	Source Voltage [V] Source current [A] Photocell					

Line	Code	Luminaire Lamps Name	Flux [lm]	Pow. [W]	Q.ty
	PX04WW	XPILL SQUARE	7850.00	80.00	1
C.I.E. F UTE	47 78 95 99 100 0.99 E + 0.01 T	D DIN 5040 B NBN	A31 BZ 5		

