

**Luminaire**

Code WDU3060NW  
Name XWIDE UGR

**Measur.**

Code WDU3060NW  
Name XWIDE UGR

Luminaire Flux	2158.83 lm	Luminaire Power	24.00 W	Efficacy	89.95 lm/W	Efficiency	91.87%
Lamps Flux	2350.00 lm	Maximum value	408.19 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	560 mm	Width	260 mm	Height	1 mm
Rectangular Luminous Area		Length	560 mm	Width	260 mm	Height	0 mm
Horizontal Luminous Area	0.145600 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.035224 m2
Coordinate system	CG	Symmetry Type		Maximum Gamma Angle		Measurement Flux	Rotosymmetrical
Date	10-06-2020	Measurement Flux		Measurement Flux		Measurement Flux	180
Measurement Distance	0.00	Measurement Flux		Measurement Flux		Measurement Flux	2350.00 lm
Operator		Source Voltage [V]		Source current [A]		Photocell	
Temperature	25.00 °C	Source current [A]		Photocell			
Humidity	60.00 %	Photocell					
Notes							

Line		Code		Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
		WDU3060NW		Name XWIDE UGR		2350.00	24.00	1
C.I.E.	62 89 97 100 92			D DIN 5040	A50			
F UTE	0.92 C			B NBN	BZ 3			

