

Luminaire

Code WDU3060WW
Name XWIDE UGR

Measur.

Code WDU3060WW
Name XWIDE UGR

Luminaire Flux	2025.63 lm	Luminaire Power	24.00 W	Efficacy	84.40 lm/W	Efficiency	91.87%
Lamps Flux	2205.00 lm	Maximum value	408.19 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Rectangular Luminous Area	Length Length	560 mm 560 mm	Width Width	260 mm 260 mm	Height Height	1 mm 0 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.145600 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.035224 m2				
Coordinate system Date Measurement Distance	CG 10-06-2020 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 180 2205.00 lm				
Operator Temperature Humidity Notes	25.00 °C 60.00 %	Source Voltage [V] Source current [A] Photocell					

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	WDU3060WW	Name XWIDE UGR	2205.00	24.00	1
C.I.E.	62 89 97 100 92	D DIN 5040	A50		
F UTE	0.92 C	B NBN	BZ 3		

