

**Luminaire**

Code WD30120WW  
Name XWIDE

**Measur.**

Code WD30120WW  
Name XWIDE

Luminaire Flux	3608.16 lm	Luminaire Power	40.00 W	Efficacy	90.20 lm/W	Efficiency	99.98%
Lamps Flux	3609.00 lm	Maximum value	334.58 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Rectangular Luminous Area	Length Length	1150 mm 1150 mm	Width Width	250 mm 250 mm	Height Height	5 mm 5 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.287500 m2 0.005750 m2 0.001250 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.005750 m2 0.001250 m2 0.075132 m2				
Coordinate system Date Measurement Distance	CG 29-05-2020 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 90 3609.00 lm				
Operator Temperature Humidity Notes	25.00 °C 60.00 %	Source Voltage [V] Source current [A] Photocell					

Luminaire Lamps						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
	WD30120WW	XWIDE	3609.00	40.00	1	
C.I.E.	45 75 94 100 100	D DIN 5040	A30			
F UTE	1.00 E	B NBN	BZ 5			

