

Luminaire

 Code WD3060NW
 Name XWIDE

Measur.

 Code WD3060NW
 Name XWIDE

Luminaire Flux	2289.47 lm	Luminaire Power	24.00 W	Efficacy	95.39 lm/W	Efficiency	99.98%
Lamps Flux	2290.00 lm	Maximum value	334.58 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Rectangular Luminous Area	Length 550 mm Length 550 mm	Width 250 mm Width 250 mm	Height 5 mm Height 5 mm				
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.137500 m2 0.002750 m2 0.001250 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.002750 m2 0.001250 m2 0.035933 m2				
Coordinate system Date Measurement Distance	CG 29-05-2020 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 90 2290.00 lm				
Operator Temperature Humidity Notes	25.00 °C 60.00 %	Source Voltage [V] Source current [A] Photocell					

Luminaire Lamps						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
	WD3060NW	XWIDE	2290.00	24.00	1	
C.I.E.	45 75 94 100 100	D DIN 5040	A30			
F UTE	1.00 E	B NBN	BZ 5			

